

**GENERATOR SPECIFICATION**

Voltage	400V
Phase	3
Frequency	50Hz
Prime Power (PRP)	6.5kVA / 5.2kW
Alternator	NSM Z100 SB
Alternator Type	Brushed with Compound
Fuel tank capacity	6.1 Litres
Autonomy 75% load	2.2 Hours
LWA	97
dBA @ 7M	72

**ENGINE SPECIFICATION**

Engine	Honda GX390
Emissions certified	EU Stage V
Cylinders	Single
Distribution	O.H.V.
Aspiration	Naturally aspirated
Cooling	Air
Displacement	389 cm <sup>3</sup>
Rpm	3000
Starting system	Recoil
Fuel	Unleaded 86 octane or higher


**DIMENSIONS (mm)**
**WEIGHT (KG)**

Length	Width	Height	71
690	480	540	


**CONTROL BOX**

- 400V: 1 x 16A BS4343 socket.
- MCB overload & short circuit protection.

**STANDARD FEATURES**

- Oil alert/low oil shutdown.
- 3 Year engine warranty (Limited).
- Full wrap-around frame.

**OPTIONS**

- Electric start.
- Long run tank.
- Trolley kit.\*

\* Different model used to illustrate trolley option.


**POWER DEFINITION**

**Prime Power (PRP)** : Applicable for supplying power to varying electrical load for unlimited hours in accordance ISO 8528-1 under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturers.